

# SERVICE SPECIFICATIONS

## TORQUE SPECIFICATIONS

| Part tightened              | N·m        | kgf·cm     | ft·lbf            |
|-----------------------------|------------|------------|-------------------|
| <b>HOOD</b>                 | —          | —          | —                 |
| Hood side hinge x Hood      | <b>23</b>  | <b>230</b> | <b>17</b>         |
| Hood lock x Body            | <b>8.0</b> | <b>75</b>  | <b>65 in.-lbf</b> |
| <b>BACK DOOR</b>            | —          | —          | —                 |
| Back door x Back door hinge | <b>29</b>  | <b>300</b> | <b>22</b>         |
| Back door hinge x Body      | <b>29</b>  | <b>300</b> | <b>22</b>         |
| <b>QUARTER WINDOW</b>       | —          | —          | —                 |
| Quarter window glass x Body | <b>4.9</b> | <b>50</b>  | <b>43 in.-lbf</b> |
| <b>SEAT</b>                 | —          | —          | —                 |
| Front Seat                  | —          | —          | —                 |
| Seat adjuster x Body        | <b>37</b>  | <b>375</b> | <b>27</b>         |
| Rear Seat                   | —          | —          | —                 |
| Seat x Seat hinge           | <b>7.8</b> | <b>80</b>  | <b>69 in.-lbf</b> |
| Seat hinge x Body           | <b>18</b>  | <b>185</b> | <b>13</b>         |
| <b>SEAT BELT</b>            | —          | —          | —                 |
| Seat belt anchor x Body     | <b>43</b>  | <b>440</b> | <b>32</b>         |
| Seat belt guide x Body      | <b>43</b>  | <b>440</b> | <b>32</b>         |