

# SERVICE SPECIFICATIONS

## SERVICE DATA

Spark plug	Type	<b>ND</b>	<b>W16EXR–U</b>
		<b>NGK</b>	<b>BPR5EY</b>
	Gap		<b>0.8 mm (0.031 in.)</b>
High–tension cord	Resistance	<b>Maximum</b>	<b>25 kΩ per cord</b>
Ignition coil	Primary coil resistance	<b>Cold</b>	<b>0.36 – 0.55 Ω</b>
	Primary coil resistance	<b>Hot</b>	<b>0.45 – 0.65 Ω</b>
	Secondary coil resistance	<b>Cold</b>	<b>9.0 – 15.4 kΩ</b>
	Secondary coil resistance	<b>Hot</b>	<b>11.4 – 18.1 kΩ</b>
Distributor	Air gap		<b>0.2 – 0.4 mm (0.008 – 0.016 in.)</b>
	Pickup coil resistance	<b>Cold</b>	<b>185 – 275 Ω</b>
	Pickup coil resistance	<b>Hot</b>	<b>240 – 325 Ω</b>

## TORQUE SPECIFICATIONS

Part tightened	<b>N·m</b>	<b>kgf·cm</b>	<b>ft·lbf</b>
Spark plug x Cylinder head	<b>18</b>	<b>180</b>	<b>13</b>
Distributor x Cylinder head	<b>19</b>	<b>195</b>	<b>14</b>