























PREPARATION**SST (SPECIAL SERVICE TOOLS)**

	09308-10010 Oil Seal Puller	
	09330-00021 Companion Flange Holding Tool	
	09504-00011 Differential Side Bearing Adjusting Nut Wrench	
	09506-30012 Differential Drive Pinion Rear Bearing Cone Replacer	
	09550-10012 Replacer Set 'B'	
	(09252-10010) No. 1 Replacer Handle	
	(09557-10010) Differential Drive Pinion Front Bearing Replacer	
	(09558-10010) Rear Axle Shaft Oil Seal Replacer	
	09554-22010 Differential Oil Seal Replacer	
	09556-30010 Drive Pinion Front Bearing Remover	
	09608-35014 Axle Hub & Drive Pinion Bearing Tool Set	
	(09608-06020) Handle	
	(09608-06110) Front Hub Inner & Drive Pinion Front Bearing Cup Replacer	

	(09608-06120) Front Hub Outer Bearing Cup Replacer	
	(09608-06180) Drive Pinion Rear Bearing Cup Replacer	
	09710-14012 Rear Suspension Bushing Tool Set	
	(09710-00010) Replacer	
	09950-00020 Bearing Remover	
	09950-30010 Puller A Set	
	09950-40010 Puller B Set	

RECOMMENDED TOOLS

	09025-00010 Torque Wrench (30 kgf-cm).	
	09031-00030 Pin Punch .	

EQUIPMENT

Dial indicator or dial indicator with magnetic base	
Micrometer	
Torque wrench	

LUBRICANT

Item	Capacity	Classification
Differential oil	4 x 4 Type 2.2 liters (2.3 US qts, 1.9 Imp. qts) 4 x 2 Type 1.8 liters (1.9 US qts, 1.6 Imp. qts)	API GL-5 Hypoid gear oil [Above – 18° C (0° F)] SAE 90W [Below – 18° C (0°F)] SAE 80W or SOW – 90